PLATE LOOP COUNT AGAR POUR PLATE METHOD IMS #3a

[Unless otherwise stated all tolerances are ±5%]

SAMPLES

1.	Laboratory Sample Requirements (see CP items 33 & 34) [For inhibitor testing requirements, refer to Section 6 of the PMO]			
			PRE-REQUISITE	
2.	Comparative Test with Standard Plate Count (SPC) (SPC – Agar Pour Plate Form 2400a)			
	a. Analyst(s) certified for SPC			
	b. Comparisons done by each analyst performing test			
		1.	Comparison is valid only if done using similar plate count methods, i.e. PCA or SMA agar with pipets (or pipettors) to PCA or SMA agar with the PLC device	
		2.	Results must be evaluated by a State/Federal LEO and shown to be acceptable prior to official use of test in laboratory	
		3.	Copy of comparison and results in QC record (or easily accessible on file in laboratory); kept for as long as analyst is certified	
			MATERIALS AND APPARATUS	
3.	Loc	р 0.0	001 mL	
	a.		e circle, welded I.D. 1.45±0.06 mm, calibrated to contain 0.001 mL, de of appropriate wire	
	 b. Loop fits over No. 54 but not a No. 53 twist drill bit (lab must have a set), checked monthly; maintain records c. Modified by making a 30° bend 3-4 mm from loop, compare to template before use 			
	d.	Орг	posite end of wire kinked in several places	
4.	Нур	ode	rmic Needle, Luer-Lok™	
	a.		gauge (sawed off 24-36 mm from the point where the barrel enters hub)	

	b.		ked end of loop wire shank inserted into needle until bend is 14 mm from end of barrel; compare to template before use	
5.	Cor	nwa	II™ Continuous Pipetting Outfit (or equivalent)	
	a.	Cor	nsisting of metal holder, Cornwall Luer-Lok syringe and filling outfit	
	b.	Syr	ringe, 2 mL capacity, adjusted to deliver 1.0 mL	
		1.	Calibrated by checking ten 1 mL discharges (10 mL) using a 10 mL Class A graduated cylinder each day of use; maintain records	
	C.	Wit	th Luer-Lok of needle attached to Luer-Lok fitting of syringe	
			PREPARATION	
6.	Ме	dia P	Preparation (reference agar from CP items 14, 27, 28 & 29)	
	a.	Ter	mperature control (TC) used	
		1.	Contains agar identical to type and volume being used	
		2.	In container identical in size and volume to that being used	
		3.	Undergoes same heat treatment and cooling as test agar	
	b.	Pla	te Count Agar or Standard Methods Agar (PCA or SMA)	
		1.	Prepare and sterilize agar for sample series and all controls	
		2.	OR use previously prepared/stored agar; melt agar quickly in boiling water or flowing steam; not under pressure	
		3.	Do not melt agar more than once	
		4.	Promptly place in a circulating water bath to temper and hold melted agar at 45±1°C	
		5.	Record agar temperature with other control information	
		6.	Discard agar that is not used within 3 hours after tempering	
		7.	Avoid prolonged exposure to high temperatures during and after melting; establish lab protocol	
7.	Hea	at Tre	eatment of Pipetting Equipment	
	a.	by v	erilize assembled Cornwall Continuous Pipetting Outfit (or equivalent) wrapping in Kraft paper or in a protective autoclavable container that mits the passage of steam and autoclave at 120±1°C for 15 min	

	b.	The pipetting outfit cannot be used for more than a 24 hour period of time without re-sterilization		
8.	Assembly of Complete Apparatus for Use			
	a.	Carefully place end of rubber supply tube (attached to syringe) in sterile dilution buffer blank and depress syringe plunger several times to pump buffer into syringe. Assure that there are no air bubbles in the syringe		
	b.	Briefly flame loop and allow to cool 15 sec		
	C.	Discharge several 1 mL portions to waste, then discharge 1 mL portion of buffer into instrument control plate (performed before testing of first sample)		
		PROCEDURE		
9.	Wor	rk Area		
	a.	Level plating bench not in direct sunlight		
	b.	Sanitize immediately before start of plating		
10.	lden	Identifying Plates		
	a.	Select number of samples in any series so that all will be plated within 20 min (pref. ≤10 min) after depositing the first sample and pouring the last plate in the series		
	b.	Label each plate with sample or control identification		
	C.	Arrange plates in order before testing begins		
		CONTROLS		
11.	Cor	ntrols (AM and PM)		
	a.	Check sterility of dilution blanks, agar, and Petri dishes used for each group of samples		
	b.	Expose a poured plate to air with cover completely removed during plating for 15 min; timer used		
		The air control plate must be the first plate poured immediately before samples are shaken and must be located such that it is in the area of the plating activity (not off to the side)		
		2. After incubation, air plate(s) shall contain <15 colonies		

		 Take and record corrective actions for air control plate(s) with >15 colonies 		
	c.	Instrument control, see item 8.c		
	d.	Determine if loop is free rinsing by preparing a rinse control plate after every 20 samples plated		
	e.	After all samples in a series have been tested, discharge a final rinse to a control plate		
	f.	Between sample series on the same day, properly protect the loop from contamination; repeat 8.b & c at the start of the next series		
	g.	Maintain records		
	h.	Include information on bench sheet, work sheet or report sheet(s)		
		DILUTING SAMPLES		
12.	San	ample Agitation		
	a.	When appropriate, wipe top of unopened containers with sterile, ethyl alcohol-saturated cloth		
	b.	Before removal of any portion, mix raw milk sample(s) by shaking 25 times in 7 sec with a 1 ft movement (containers approx ¾ full); use within 3 min		
13.	Inoc	culating Plates		
	a.	Dip loop into sample (avoid foam and bubbles) to bend in shank and withdraw vertically from surface three times in 3 sec with uniform movement of 2.5 cm		
	b.	Raise cover of Petri dish (just high enough to insert loop), insert loop and depress plunger causing sterile dilution buffer to flow down the shank, across charged loop washing measured 0.001 mL of sample into dish		
	C.	Do not depress plunger so rapidly that buffer fails to flow across loop		
14.	Pou	ring Agar		
	a.	After dispensing test portions, promptly pour 10-12 mL agar into each plate of series, or 12-15 mL where agar weight loss is a problem that cannot be corrected by other actions (Documentation must be kept to indicate that this is a routine practice; amount poured to match agar weight loss test)		

		1.	Lift cover of Petri dish just high enough to pour agar			
		2.	After agar is poured, thoroughly and evenly mix agar and test portion in Petri dish(es)			
			a. Agar solidification to occur within 10 min			
			b. Do not stack plates prior to solidification			
			INCUBATION			
15.	Incu	ubati	ng Plates (see CP item 15)			
	a.		ck plates (upside down) no more than 6 high and incubate within min of agar solidification			
	b.	Place stacks to ensure adequate air flow				
	C.	Incu	ubate PLC plates at 32±1°C for 48±3 hours			
			COUNTING COLONIES			
16.	Cou	ounting Aids (see CP items 16 & 17)				
	a.		unt colonies with Quebec dark-field model or equivalent with sfactory grid plate (see CP item 16)			
	b.	Han	nd tally (see CP item 17)			
17.	Cou	ounting, Recording and Computing PLC				
	a.	Afte	er incubation count all colonies on plates			
	b.		ere impossible to count at once, store plates at 0.0-4.5°C for not ger than 24 hr (avoid as a routine practice)			
	c.	Rec	cord results of sterility and control tests			
	d.	Rec	cord number of colonies on the plate counted			
	e.					
		1.	Use higher magnification if necessary to distinguish colonies from foreign matter			
		2.	Examine edge of Petri dishes for colonies			

f.	Spreaders				
	1.	Count colonies on representative portion only when colonies are well distributed and area covered or repressed does not exceed 25% of plate			
	2.	Do not count if repressed growth area > 25% of plate area			
	3.	When spreaders must be counted, count each as a single colony			
	4.	Count chains/spreaders from separate sources as separate colonies			
	5.	If 5% of plates are more than 25% covered by spreaders, take Immediate steps to eliminate and resolve problem			
g.	If plate exceeds 250 colonies, estimate counts as follows				
	1.	Count colonies in portions representative of distribution and estimate the total			
	2.	Where there are < 10 colonies/sq. cm, count colonies in 12 squares, selecting 6 consecutive squares horizontally across the plate and 6 consecutive squares at right angles			
	3.	When there are 10 or more colonies/sq. cm, count 4 random representative squares			
	4.	Multiply average number colonies/sq. cm by area of plate in sq. cm			
h.	If pla	ate yields < 25 colonies, record actual number			
i.	If the plate shows no colonies, record count as 0				
j.	Multiply number of colonies (or estimated number if necessary) by 1,000				
lder	Identifying Counting Errors				
a.	Perform monthly counting for PLC				
	1.	With 3 or more analysts, use the RpSm method (see current SMEDP); maintain records			
	2.	With two analysts, comparative counts agree within ≤ 10% of one another; maintain records			
	3.	If only one analyst, replicate counts agree within 8% of one			

18.

REPORTING

19.	Reporting – refer to CP, item 34.b.2.d [When samples are demonstrated to contain inhibitors, no bacteria counts are reported; report as positive for inhibitors or growth inhibitors (GI)]					
	a.	Report computed count as Plate Loop Count/mL (PLC/mL) when taken from a plate in the 25-250 range				
	b.	Report PLC plate counts of 0 to 24 as < 25,000 Estimated PLC (EPLC)				
	C.	When colonies on plate exceed 100/sq. cm, compute count by multiplying 100 x dilution factor x area of plate in sq. cm and report as > computed Count Estimated (EPLC)				
	 d. If computed count from PLC plate is > 250, report as Estimated PLC (EPLC) 					
	e.	If for any reason, an entire plate is not counted, the computed count is reported as Estimated (EPLC)				
	f.	Report only first two left-hand digits				
		If the third digit is 5 round the second number using the following rules				
		a. When the second digit is odd round up (odd up, 235 to 240)				
		b. When the second digit is even round down (even down, 225 to 220)				
	g.	If the plate from a sample has excessive spreader growth, report as spreaders (SPR)				
	h. If a laboratory accident renders a plate uncountable, report as laboratory accident (LA)					